


IEC Appliance Outlet H, Screw-on Mounting, Solder Terminal



**Description**

- 1 Function: Connector,
- Pin temperature 70 °C, Protection class II, Cable

**Weblinks**

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [REACH](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [CAD-Drawings](#), [Accessories](#), [Detailed request for product](#)

**Technical Data**

Ratings IEC	10 A / 250 VAC; 50 Hz
Ratings UL/CSA	10 A / 250 VAC; 60 Hz
Dielectric Strength	> 2 kVAC between L-N > 2 kVAC between L/N-PE (1 min/50Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 20 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class II acc. to IEC 61140
Terminal	Cable
Panel Thickness s	Screw 0.5 Nm Snap-in 1 mm
Material: Housing	PA6, black, UL 94V-0

**Config. Code**


5099 - H - A B C 0 - D - E J

The characters are placeholders for the correspondingly keys of selections from the key tables.

5099 - H - A B C 0 - D - E J = Type

Type	Configuration key
protection class 2	B

5099 - H - A B C 0 - D - E J = Terminals

Terminal L	Configuration key
solder terminal 	1

5099 - H - A B C 0 - D - E J = Terminals

Terminal N	Configuration key
solder terminal	1
Symbols similar as in table A	

5099 - H - A B C 0 - D - E J = Terminals

Terminal Ground	Configuration key
without terminal	0
Symbols similar as in table A	

5099 - H - A B C 0 - D - E J = Color

Color	Configuration key
Black	A

5099 - H - A B C 0 - D - E J = Style

Style	Configuration key
insert type	5

5099 - H - A B C 0 - D - E **J** = Condition

Condition	Configuration key

PHASE-OUT