

fuse GLDIII 500V, super quick acting



See below:  
[Approvals and Compliances](#)

### Description

- Characteristic gR
- According to IEC 269
- According VDE 0636
- Protection of semiconductors
- Time-current characteristic on request
- Cut-off current characteristic on request

### Technical Data

Rated Current In	35- 63A
Rated Voltage	500VAC
Breaking Capacity	50kA
Rated Power Operating Frequency fe	50Hz

### Basic Design

Insulator	Ceramics
Metal components	Brass

### Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

### Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
<a href="#">REACH</a>	<a href="#">REACH</a>	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

### All Variants

Rated current [A]	Style [Compact]	Power Loss [W]	Order Number	E-No.
35	-	-	0034.1112	800323509
50	-	-	0034.1114	800325009
63	-	-	0034.1115	800326009

Availability for all products can be searched real-time:<https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

**Packaging unit** 5 Pcs